

KEY FEATURES


- > Low voltage piezo ceramic
- > Optimal preload for high dynamics
- > High Efficiency
- > Compact Size
- > High Resolution

RELATED PRODUCTS

- > CTEC benchtop controllers
- > CTEC OEM controllers

AVAILABLE OPTIONS

- > SG sensor
- > Vacuum compatibility
- > Ultra High Vacuum
- > Non magnetic shell



NON CONTRACTUAL PICTURE

PARAMETER	VALUE	UNIT
> Quasistatic performances		
Nominal Stroke	44	μm
Min stroke	40	μm
Resolution ⁽¹⁾	2.5	nm
Blocked force	3 500	N
Stiffness	110	N/μm
> Dynamic performances		
Resonance frequency (free-free) ⁽²⁾	15000	Hz
Resonance frequency (blocked-free) ⁽³⁾	8 300	Hz
Force limit ⁽⁴⁾	1 500	N
> Control & driving		
Voltage range	-20 ... 150	V
Capacitance ⁽⁵⁾	8.8	μF
> Dimensions & interfaces		
Height	57	mm
Length	24	mm
Width incl wires	18	mm
Mass	92	g
> Standard mechanical interfaces	See ICD	
> Electrical interface	See ICD	

ANNOTATIONS

(1) Quasistatic excitation. With standard LA75 range amplifier. SNR=85dB computed as RMS output signal /RMS output Noise floor at [0;200Hz]

(2) Free-free: The actuator mounts are free

(3) Blocked-free: The actuator is fixed to a mechanical support assumed infinitely stiff

(4) Maximum pulling or pushing external force, valid up to 90% of the blocked-free resonance frequency of the actuator

(5) Capacitance +/- 20%, at 1 V RMS, low frequency, without load

